



## Dimensions

<b>Width</b>	541 mm
<b>Height</b>	600 mm
<b>Depth</b>	365 mm
<b>Flue Diameter</b>	127 mm
<b>Height of stand</b>	136 mm
<b>Height of log store</b>	386 mm
<b>Total height on stand</b>	736 mm
<b>Total height on log store</b>	986 mm
<b>Height to centre of rear flue</b>	484 mm
<b>Depth from back to centre of top flue</b>	108 mm
<b>Ideal log length</b>	380 mm

## Performance — Wood Fuel

	<b>Wood Fuel</b>
<b>Energy Efficiency Class</b>	A
<b>Nett Efficiency</b>	79.3 %
<b>Nominal Output</b>	4.9 kW
<b>Mean Co Emission (@13% O2)</b>	0.21 %
<b>Mean Co2 Emission(@13% O2)</b>	-
<b>DIN+ particulate</b>	-
<b>Mean NOx Emission (@13% O2)</b>	-
<b>Mean OGC Emission(@13% O2)</b>	-
<b>Flue Gas Mass Flow</b>	6.96 g/s
<b>Flue Gas Temperature</b>	178.4 °C

## Product Fiche

<b>Supplier name</b>	Arada
<b>Product Code</b>	SOL5MCE-WSsn
<b>Energy Efficiency Class (wood)</b>	A
<b>Direct Heat Output (wood)</b>	4.9 kW
<b>Indirect Heat Output (wood)</b>	N/A
<b>Energy Efficiency Index (wood)</b>	105.9
<b>The useful energy efficiency at nominal heat output and at minimum load (wood)</b>	79.3 %

### Specific precautions that shall be taken when the local space heater is assembled, installed or maintained:

Product should be installed in accordance with local building regulations.  
Appliance will become very hot during use.

## Features

<b>Flexifuel</b>	No
<b>Stove body type</b>	Freestanding
<b>Ecodesign Ready</b>	No
<b>Suitable for smoke control areas</b>	No
<b>Suitable for direct air connection</b>	No
<b>Suitable for non-combustible 12mm hearth</b>	Yes
<b>Max hearth temperature</b>	62.9 °C
<b>Weight gross (packed weight)</b>	57 Kg
<b>Weight nett (unpacked weight)</b>	78 Kg

## Minimum distance to combustibles

<b>To Rear</b>	<b>To Side</b>	<b>Above</b>
300 mm	300 mm	381 mm