



Dimensions

Width (across footprint)	485 mm
Height	660 mm
Depth (from rear to tip of handle)	389 mm
Flue Diameter	-
Depth from back to centre of top flue	120.5 mm
Height to centre of rear flue	520 mm

Flue Type	Balanced Flue			
Gas type				
Gas Types	A = G20 I2H, I2E B = G20 I2H, I2E C = G25/G25.3 I2L, I2EK I2(43.46-45.3 MJ/m³ (OC))			
	A	B	C	D
Supply pressure Mbar	20	20 / 25	25	20
Nominal Heat Input Gross (Hs) kW	5	5 / 4.3	4.3	4
Nominal Heat Input Gross (Hi) kW	4.5	4.5 / 3.9	3.9	3.6
Consumption M3/hr	0.471	0.47 / 0.58	0.58	0.47
Burner pressure (Hot) mbar	19.4	19.4 / 24	24	19.3

Injector Marking	320
Pilot	G30-ZP2-312 (31.2 inj)
Efficiency Class 1	C
Nox Class	5
Flue System Types	C11 / C31 / C91
Gas Types	A = G20 I2H, I2E B = G20 I2H, I2E C = G25/G25.3 I2L, I2EK I2(43.46-45.3 MJ/m ³ (OC)) D = G20/G25 I2ELL

Product Fiche

Supplier name	Arada
Product Code	HOLGAS-M-NG-BF
Energy Efficiency Class	C
Energy Efficiency Index	83.5
Direct Heat Output	4.5 kW
Nominal Heat Output: High	4.5 kW
Nominal Heat Output: Low	-
Indirect Heating Functionality	N/A
Indirect Heat Output	N/A
Useful Energy Efficiency Net CV : High	-

Useful Energy Efficiency Net CV : Low	-
---------------------------------------	---

Heat Output Control	Electronic room temperature control plus day timer
Permanent Pilot Power kW	N/A
Space Heating Emissions NOx (GCV)	-

Specific precautions that shall be taken when the local space heater is assembled, installed or maintained:

Product should be installed in accordance with local building regulations. The installer must be Gas Safe Registered. Appliance will become very hot during use.

Flue type	Balanced flue
Gas connection	8mm compression
Remote gas valve	TESC 01 RF868-15
Countries of destination	GB & IE
Space heating emissions NOx (GCV)	95 mg/kWh
Hearth requirement	12mm thick and of non-combustible material. Hearth must extend 100mm in front of appliance
Weight gross (packed weight)	64.2 Kg

Minimum distance to materials

Position	Non-combustible material	Combustible material
Above	100 mm	300 mm
Back	50 mm	300 mm
Left	50 mm	300 mm
Right	50 mm	300 mm

This appliance must be installed with a minimum clearance to non-combustible materials of 50mm rear and sides. We recommend clearance of 300mm to combustible beams above the stove.. Installation and operating instructions for this stove are available online at www.aradastoves.com.