



## Product Fiche

Supplier Name or Brand	Arada Ltd
Product Code	i600SLF-L-BK-G2
Energy Efficiency Class	A
Direct Heat Output	4.9 kW
Energy Efficiency Index	101.2
The useful energy efficiency at nominal heat output and at minimum load	75.9 %

Specific precautions that shall be taken when the local space heater is assembled, installed or maintained:  
*Product should be installed in accordance with local building regulations. Appliance will become very hot during use.*

## Dimensions

Width	659 mm
Height	585 mm
Depth	372 mm
Flue Diameter	127 mm
Height to centre of rear flue	470 mm
Depth from back to centre of top flue	102 mm
Ideal log length	480 mm

## Features

Flexifuel	Yes
Stove body type	Freestanding
Suitable for Smoke Control Areas	Yes
Suitable for direct air connection	Yes
Suitable for non-combustible 12mm hearth	Yes
Max hearth Temperature	31 °C

## Minimum Distance To Combustibles

To Rear	To Side	Above
350 mm	200 mm	381 mm

## Performance - Wood & Solid Fuel

	Wood Fuel	Smokeless Solid Fuel
Energy Efficiency Class	A	
Nett Efficiency	75.9 %	%
Nominal Output	4.9 kW	4.9 kW
DIN+ particulate	Nmg/m3	Nmg/m3
Mean Co Emission(@13% O2)	0.28 %	%
Mean Co2 Emission(@13% O2)	%	%
Mean NOx Emission(@13% O2)	Nmg/m3	Nmg/m3
Mean OGC Emission(@13% O2)	Nmg/m3	Nmg/m3
Flue Gas Mass Flow	4.9 g/s	-
Flue Gas Temperature	275 °C	-