



## Product Fiche

<b>Supplier name</b>	Arada
<b>Product Code</b>	I600SLF-M-BK-G2
<b>Energy Efficiency Class (wood)</b>	A
<b>Direct Heat Output (wood)</b>	4.9 kW
<b>Indirect Heat Output (wood)</b>	N/A
<b>Energy Efficiency Index (wood)</b>	101.2
<b>The useful energy efficiency at nominal heat output and at minimum load (wood)</b>	75.9 %

### Specific precautions that shall be taken when the local space heater is assembled, installed or maintained:

Product should be installed in accordance with local building regulations. Appliance will become very hot during use.

## Features

<b>Flexifuel</b>	Yes
<b>Stove body type</b>	Freestanding
<b>Ecodesign Ready</b>	No
<b>Suitable for smoke control areas</b>	Yes
<b>Suitable for direct air connection</b>	Yes
<b>Suitable for non-combustible 12mm hearth</b>	Yes
<b>Max hearth temperature</b>	36.2 °C
<b>Weight gross (packed weight)</b>	109 Kg

## Dimensions

<b>Width</b>	659 mm
<b>Height</b>	790 mm
<b>Depth</b>	372 mm
<b>Flue Diameter</b>	127 mm
<b>Height to centre of rear flue</b>	675 mm
<b>Depth from back to centre of top flue</b>	102 mm
<b>Ideal log length</b>	480 mm

## Minimum distance to combustibles

To Rear	To Side	Above
350 mm	200 mm	381 mm

## Performance—Wood Fuel

	Wood Fuel
<b>Energy Efficiency Class</b>	A
<b>Nett Efficiency</b>	75.9 %
<b>Nominal Output</b>	4.9 kW
<b>Output Range</b>	3.6 – 6.1 kW
<b>Mean Co Emission (@13% O<sub>2</sub>)</b>	0.28 %
<b>Mean Co<sub>2</sub> Emission (@13% O<sub>2</sub>)</b>	-
<b>DIN+ particulate</b>	-
<b>Mean NO<sub>x</sub> Emission (@13% O<sub>2</sub>)</b>	-
<b>Mean OGC Emission (@13% O<sub>2</sub>)</b>	-
<b>Flue Gas Mass Flow</b>	4.9 g/s
<b>Flue Gas Temperature</b>	275 °C