

DECLARATION OF PERFORMANCE - Regulation (EU) 305/2011



Manufacturer: Arada Ltd, The Fireworks, Weycroft Avenue, Axminster Devon, United Kingdom EX13 5HU

Trade Mark Brand: Hamlet

Range Designation: Solution S4 Inset Stoves

Intended Use: Inset Domestic Heating Appliance

Independent Performance and Safety tested : UKCA - Kiwa Gastec, Notified Body No: 0558

CE - Kiwa Cermet Italia S.p.A, Notified Body No. 0476

Constancy of Performance System AVCP: System 3

Model	SOLUTION 5 INSET S4	SOLUTION 7 INSET S4
Internal Product Code :	SOL5-INSET-S4	SOL7-INSET-S4
Approximate Output Range: (kW)	4.1 - 6.7	5 - 8.6
Harmonised EN European Standard (hEN):	BS EN 13229:2001 + A1:2003 + A2:2004	BS EN 13229:2001 + A1:2003 + A2:2004
Additional Characteristics Test Standard:	DIN+	DIN+
Additional Particulate Emission Test Standard:	PD6434	PD6434
Test Report reference:	61276-7	61276-4
Performance Characteristics on Wood Fuel		
Total Efficiency: (%)	79.9	75.4
Declared nominal output: (kW)	5	7
Tested nominal Output: (kW)	5	7.1
Flue gas mass flow: (g/s)	4.1	6.2
Mean CO emission (@13% O ₂) : (%)	0.08	0.11
Mean OGC emission (@13% O ₂): (Nmg/m ³)	79	92
Mean NO _x emission (@13% O ₂): (Nmg/m ³)	97	95
DIN+ particulates (@13% O ₂): (Nmg/m ³)	14	27
PD6434 Particulate Emissions High output: (gh-1)	2.7	2.3
PD6434 Particulate Emissions Low output: (gh-1)	1.8	1.2
Mean Flue Temperature: (Deg C)	274	326
Underhearth Temperature: (Deg C)	66	70
Approximate Max Log Length: (mm)	200	300
Performance Characteristics on Maximite Briquetted Smokeless Fuel		
Total Efficiency: (%):	76	75.5
Declared nominal output: (kW)	5	7
Tested nominal output: (kW)	5	7.1
Flue gas mass flow: (g/s)	4.1	6.4
Mean CO emission (@13% O ₂) : (%)	0.07	0.08
Mean OGC emission (@13% O ₂): (Nmg/m ³)	30	43
Mean NO _x emission (@13% O ₂): (Nmg/m ³)	138	159
DIN+ particulates (@13% O ₂): (Nmg/m ³)	12	27
Mean Flue Temperature: (Deg C)	323	332
Underhearth Temperature: (Deg C)	66	70
Safety Distances from Combustibles (standard flue connection)		
Side Wall: (mm)	175	175
Top Shelf: (mm)	250	200
Safety Distances from Combustibles (twin wall flue connection)		
Side Wall: (mm)	N/A	N/A
Rear Wall: (mm)	N/A	N/A

The performance of the product identified above is in conformity with the set of declared performance.

This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011 as it has effect in the United Kingdom in respect of Great Britain, under the sole responsibility of the manufacturer identified above.

Signed on behalf of the manufacturer:

ARADA
DEVON
J. Stantford

18 February 2025