

'TESC' gas valve remote control error codes for Arada Ecoburn Gas and Holborn Gas models

Updated: 18/01/2023

Note: The information provided below is for the benefit of service engineers only.

Your gas fire appliance contains no user-servicable parts inside and must be serviced and checked annually only by a suitably qualified Gas Safe heating engineer.

If you believe your appliance is not working correctly or it has broken down, in the first instance please contact your local retailer or installer for assistance. Please refer to the accompanying user guide for details of your guarantee.

Error codes

Error codes appear on the handset to assist in diagnosis in the event of a gas fire failing to start. Error codes will appear if the control detects abnormal conditions with the fire, either in environment, in installation, failure of components or the internal electronics.

Note: To reset any error code, press and hold the power button on the valve.

Note: If the batteries are faulty or lack sufficient power to operate the valve this can also lead to false error codes being shown.

Video to accompany some of the issues mentioned below can be found on the <u>Arada Stoves YouTube</u> <u>channel</u>

Error code list:

- <u>E02</u>
- <u>E06 or E07</u>
- <u>E09</u>
- <u>E10</u>
- <u>E32</u>
- <u>E34</u>
- <u>E36, E38, E41 or E42</u>
- <u>E45</u>

- <u>E48</u>
- <u>E51</u>
- <u>E52 or E56</u>

E00

Description of error	
No flame at pilot	
No heat to thermocoupling	

No heat to thermocoupling
Action
☐ Check batteries for low power
☐ Check gas to appliance, has it been purged
☐ Check for, and clear any dust in pilot filter
☐ Check for bad connections to Thermocouple
☐ Else, replace gas valve
Important notes First call always is to check batteries first.
E02
Description of error
Overheating
Action
☐ Check for spillage
☐ Check Mica in burner
☐ Check air relief to the appliance
☐ Check gas pressure and gas rate
☐ Check that the position of the ceramics is correct
Important notes
Has the appliance been serviced and ODS changed?
E06 or E07

Description of error

No power

Action

 $\hfill \square$ Replace batteries with decent alkaline batteries

☐ Check power lead is plugged in and not broken
Important notes
Re-check batteries are inserted correctly
E09
Description of error
Device connected to TESC is not functioning correctly
Action
☐ Check external devices, switches etc.
☐ Else, replace gas valve
Important notes
Gas supply to to the appliance
E10
Description of error
Device connected to TESC is not functioning correctly
Action
Normally on a stove, check TTB connection also check fuel layout. If not corrrect a large flame can
overheat the body of the stove and effect the TTB.
Important notes
Thermocouple connections red on outside of valve
E32
Description of error
Self test procedure fails
Action
☐ Check batteries
☐ Else, replace gas valve
Important notes
If touch control fitted, check ribbons are aligned correctly

E34 **Description of error** Pllot light fails to activate, error code appears on remote after a few seconds **Action** ☐ Replace (3 x AA) TESC Gas valve batteries E36, E38, E41 or E42 **Description of error** Gas valve jammed **Action** Replace gas valve Important notes The Handset comes already paired with the fire. Trying to re-pair the handset at any time does nothing E45 **Description of error** USED ONLY DURING MANUFACTURER OF VALVE **Action** Replace gas valve E48 **Description of error** Error on thermocouple

E51

Check batteries

☐ Else, replace gas valve

Action

☐ Check leads are correct, spade on valve, red to outside

☐ Check age of TC, replace annually at service

☐ Check insulation on TC is not broken on sharp metalwork

Description of error
Error with extension from gas valve
Action
☐ Check any switches connected to the gas valve
☐ Else, replace gas valve
E52 or E56
Description of error
Self-test procedure fails
Action
☐ Check batteries
☐ Else, replace gas valve