

Arrow INSET STOVE 750 (i750) stove

Product Fiche

Supplier Name or Brand	Arada Ltd
Product Code	i750
Energy Efficiency Class	Not applicable
Direct Heat Output	8.9 kW
Energy Efficiency Index	Not applicable
The useful energy efficiency at nominal heat output and at minimum load	77.5 %

Specific precautions that shall be taken when the local space heater is assembled, installed or maintained: *Product should be installed in accordance with local building regulations. Appliance will become very hot during use.*

Features

Flexifuel	Yes
Stove body type	Cassette
Suitable for Smoke Control Areas	Yes
Suitable for direct air connection	No
Suitable for non-combustible 12mm hearth	No
Flue outlet	Vertical Spigot
Weight gross (packed kg)	108 Kg

Dimensions

Width	762 mm
Height	558 mm
Depth	407 mm
Flue Diameter	127 mm
Depth into fireplace	351 mm
Width into fireplace	760 mm
Height into fireplace	556 mm
Depth from back to centre of top flue	100 mm
Ideal log length	600 mm

Please note: Dimensions do not include optional trims where shown

Minimum Distance To Combustibles

To Side	Above
150 mm	600 mm

Optional Extras

Trim For I750 3 Sided - Standard (30mm) - [TRIM018]
 Trim For I750 3 Sided - Wide (60mm) - [TRIM030]
 Trim For I750 4 Sided - Standard (30mm) - [TRIM024]
 Trim For I750 4 Sided - Wide (60mm) - [TRIM036]
 Wide Trim For I750 - [TRIM012]